

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

08/31/1999 NVILLARI 00000047 500417 09374041

01 FC:108 760.00 CH

02 FC:110 18.00 CH

10/27/2000 JWASHING 00000013 500417 09374041

01 FC:105 130.00 CH

08/13/99
JC639 U.S. PTO

cket No.: 50246-068

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


In re Reissue of U.S. Patent 5,598,525

Issued January 28, 1997

To Robert M. Nally, et al.

Based on Serial No.: 376,919

Filed: January 23, 1995



Group Art Unit:

Examiner:

For: APPARATUS, SYSTEMS AND METHODS FOR CONTROLLING GRAPHICS AND VIDEO
DATA IN MULTIMEDIA DATA PROCESSING AND DISPLAY SYSTEMS

REISSUE APPLICATION TRANSMITTAL

Box 7

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Transmitted herewith is an application for reissue of U.S. Patent No. 5598525 issued on January 23, 1995 to
inventors Robert M. Nally and John C. Schafer.

Enclosed are the following:

SPECIFICATION, CLAIMS AND DRAWINGS

- (a) ☒ 14 pages of specification and cover page
☒ 9 pages of claims
☒ 1 page of abstract
(b) ☐ sheets of formal drawings
☐ No changes in the drawings upon which the original patent was issued are to be made. Therefore, in accordance with 37 CFR §1.174, please find attached, in the size required for original drawings:
☒ a copy of the printed drawings of the patent (4 sheets)
☐ a photoprint of the original drawings.

2. DECLARATION AND POWER OF ATTORNEY

- ☒ 12 pages of declaration and power of attorney (unsigned)

Jc135 U.S. PTO
09/374041
08/13/99

3. PRELIMINARY AMENDMENT
attached

4. OFFER TO SURRENDER THE ORIGINAL LETTERS PATENT IN ACCORDANCE WITH 37 CFR §1.178
☒ attached (unsigned)

5. LETTERS PATENT
☐ original letters patent attached
☐ declaration that original letters patent lost or inaccessible

6. TITLE
In accordance with 37 CFR §1.171, this application for reissue is accompanied by:
☐ a certified copy of an abstract of title
or
X Certificate under 37 C.F.R. 3.73(b)

7. INFORMATION DISCLOSURE STATEMENT
☒ attached with 21 Exhibits

PRIORITY - 35 USC §119
☐ Priority of Patent Application filed on in is claimed under 35 USC §119.
☐ The certified copies have been filed in prior application Serial No. filed on .

FEE CALCULATION (37 CFR §1.16(i) AND (j))
Claims as Filed:

	NO. OF CLAIMS		EXTRA CLAIMS	RATE	AMOUNT
Total Claims	48	-20		\$18.00 =	\$504.00
Independent Claims	6	-3		\$78.00 =	\$234.00
Basic Application Fee					\$790.00
Fee for Title Report					0
Total Application Fee					\$1528.00
Subtract ½ if small entity					
TOTAL APPLICATION FEE DUE					\$1528.00
AMOUNT TO BE CHARGED TO DEPOSIT ACCOUNT NO. 500417					\$1528.00

10. SMALL ENTITY STATUS (if applicable)
☐ A verified statement that this filing is by a small entity is attached

11. ASSIGNMENT INFORMATION (if applicable)

☒ The prior application is assigned of record to . Cirrus Logic, Inc. See Certificate under 37 C.F.R. 3.73(b), attached.

12. METHOD OF PAYMENT OF FEES

☒ Charge Deposit Account No. 500417 in the amount of \$ 1510.00. Two copies of this request are attached.

13. AUTHORIZATION TO CHARGE ADDITIONAL FEES

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication and during the entire pendency of this application or credit any overpayment to Deposit Account No. 500417. Two duplicate copies are enclosed.

- ☒ 37 CFR §1.16 (filing fees)
- ☒ 37 CFR §1.16 (presentation of extra claims)
- ☒ 37 CFR §1.16(e) (surcharge for filing the basic filing fee and/or declaration on a date later than the filing date of the application.
- 37 CFR §1.17 (application processing fees)
- 37 CFR §1.18 (issue fee at or before mailing of Notice of Allowance, Pursuant to 37 CFR 1.§311(b).

Respectfully submitted,

MCDERMOTT, WILL & EMERY



David L. Stewart
Registration No. 37,578

500 13th Street, N.W.
Washington, DC 20005-3096
(202) 756-8000 DLS:pgb

Date: August 13, 1999

Facsimile: (202) 756-8087

APPARATUS, SYSTEMS AND METHODS FOR CONTROLLING GRAPHICS AND VIDEO DATA IN MULTIMEDIA DATA PROCESSING AND DISPLAY SYSTEMS

5

TECHNICAL FIELD OF THE INVENTION

The present invention relates in general to multimedia processing and display systems and in particular to apparatus, systems and methods for controlling graphics and video data overlay in multimedia processing and display systems.

10

CROSS-REFERENCE TO RELATED APPLICATIONS

The following copending and coassigned United States patent applications contain related information and are incorporated herein by reference:

15

U.S. patent application Ser. No. 08/098,846 (Attorney's Docket No. P3510-P11US), entitled "System And Method For The Mixing Of Graphics And Video Signals," and filed Jul. 29, 1993; and

20

U.S. patent application Ser. No. 08/223,845 (Attorney's Docket No. P3510-P21US), entitled "Apparatus, Systems And Methods For Processing Video Data In Conjunction With A Multi-Format Frame Buffer," and filed Apr. 6, 1994.

25

BACKGROUND OF THE INVENTION

As multimedia information processing systems increase in popularity, system designers must consider new techniques for controlling the processing and display of data simultaneously generated by multiple sources. In particular, there has been substantial demand for processing systems which have the capability of concurrently displaying both video and graphics data on a single display screen. The development of such systems presents a number of design challenges, not only because the format differences between graphics and video data must be accounted for, but also because of end user driven requirements that these systems allow for flexible manipulation of the data on the display screen.

30

35

40

One particular technique for simultaneously displaying video and graphics data on a single display screen involves the generation of "windows." In this case, a stream of data from a selected source is used to generate a display within a particular region or "window" of the display screen to the exclusion of any non-selected data streams defining a display or part of a display corresponding to the same region of the screen. The selected data stream generating the display window "overlays" or "occludes" the data from the nonselected data streams which lie "behind" the displayed data. In one instance, the overall content and appearance of the display screen is defined by graphics data and one or more "video windows" generated by data from a video source occlude a corresponding region of that graphics data. In other instances, a video display or window may be occluded or overlaid by graphics data or even another video window.

45

50

55

In the multimedia environment, the "windowing" described above yields substantial advantages. Among other things, the user can typically change the size and location on the display screen of a given window to flexibly manipulate the content and appearance of the data being displayed. For example, in the case of combined graphics and video, the user can advantageously create custom composite visual displays by combining multiple video and graphics data streams in windowing environment.

60

65

U.S. Pat. No. 5,440,000
U.S. Pat. No. 5,440,001
U.S. Pat. No. 5,440,002
U.S. Pat. No. 5,440,003
U.S. Pat. No. 5,440,004
U.S. Pat. No. 5,440,005
U.S. Pat. No. 5,440,006
U.S. Pat. No. 5,440,007
U.S. Pat. No. 5,440,008
U.S. Pat. No. 5,440,009
U.S. Pat. No. 5,440,010
U.S. Pat. No. 5,440,011
U.S. Pat. No. 5,440,012
U.S. Pat. No. 5,440,013
U.S. Pat. No. 5,440,014
U.S. Pat. No. 5,440,015
U.S. Pat. No. 5,440,016
U.S. Pat. No. 5,440,017
U.S. Pat. No. 5,440,018
U.S. Pat. No. 5,440,019
U.S. Pat. No. 5,440,020
U.S. Pat. No. 5,440,021
U.S. Pat. No. 5,440,022
U.S. Pat. No. 5,440,023
U.S. Pat. No. 5,440,024
U.S. Pat. No. 5,440,025
U.S. Pat. No. 5,440,026
U.S. Pat. No. 5,440,027
U.S. Pat. No. 5,440,028
U.S. Pat. No. 5,440,029
U.S. Pat. No. 5,440,030
U.S. Pat. No. 5,440,031
U.S. Pat. No. 5,440,032
U.S. Pat. No. 5,440,033
U.S. Pat. No. 5,440,034
U.S. Pat. No. 5,440,035
U.S. Pat. No. 5,440,036
U.S. Pat. No. 5,440,037
U.S. Pat. No. 5,440,038
U.S. Pat. No. 5,440,039
U.S. Pat. No. 5,440,040
U.S. Pat. No. 5,440,041
U.S. Pat. No. 5,440,042
U.S. Pat. No. 5,440,043
U.S. Pat. No. 5,440,044
U.S. Pat. No. 5,440,045
U.S. Pat. No. 5,440,046
U.S. Pat. No. 5,440,047
U.S. Pat. No. 5,440,048
U.S. Pat. No. 5,440,049
U.S. Pat. No. 5,440,050
U.S. Pat. No. 5,440,051
U.S. Pat. No. 5,440,052
U.S. Pat. No. 5,440,053
U.S. Pat. No. 5,440,054
U.S. Pat. No. 5,440,055
U.S. Pat. No. 5,440,056
U.S. Pat. No. 5,440,057
U.S. Pat. No. 5,440,058
U.S. Pat. No. 5,440,059
U.S. Pat. No. 5,440,060
U.S. Pat. No. 5,440,061
U.S. Pat. No. 5,440,062
U.S. Pat. No. 5,440,063
U.S. Pat. No. 5,440,064
U.S. Pat. No. 5,440,065
U.S. Pat. No. 5,440,066
U.S. Pat. No. 5,440,067
U.S. Pat. No. 5,440,068
U.S. Pat. No. 5,440,069
U.S. Pat. No. 5,440,070
U.S. Pat. No. 5,440,071
U.S. Pat. No. 5,440,072
U.S. Pat. No. 5,440,073
U.S. Pat. No. 5,440,074
U.S. Pat. No. 5,440,075
U.S. Pat. No. 5,440,076
U.S. Pat. No. 5,440,077
U.S. Pat. No. 5,440,078
U.S. Pat. No. 5,440,079
U.S. Pat. No. 5,440,080
U.S. Pat. No. 5,440,081
U.S. Pat. No. 5,440,082
U.S. Pat. No. 5,440,083
U.S. Pat. No. 5,440,084
U.S. Pat. No. 5,440,085
U.S. Pat. No. 5,440,086
U.S. Pat. No. 5,440,087
U.S. Pat. No. 5,440,088
U.S. Pat. No. 5,440,089
U.S. Pat. No. 5,440,090
U.S. Pat. No. 5,440,091
U.S. Pat. No. 5,440,092
U.S. Pat. No. 5,440,093
U.S. Pat. No. 5,440,094
U.S. Pat. No. 5,440,095
U.S. Pat. No. 5,440,096
U.S. Pat. No. 5,440,097
U.S. Pat. No. 5,440,098
U.S. Pat. No. 5,440,099
U.S. Pat. No. 5,440,100

In order to efficiently control windows in a multimedia environment efficient frame buffer management is required. Specifically, a frame buffer control scheme must be developed which allows for the efficient storage and retrieval of multiple types of data, such as video data and graphics data. To be cost competitive as well as functionally efficient, such a scheme should minimize the number of memory devices and the amount of control circuitry required and should insure that data flow to the display is subjected to minimal delay notwithstanding data type.

One of the major difficulties in managing video in a combined video and graphics windowing environment results from the fact that the video data being received and displayed are constantly being updated, typically at a rate of thirty frames per second. In contrast, the graphics data are normally generated once to define the graphics display and then remain static until the system CPU change that graphics display. Thus, the occlusion (overlay) of video data with graphics data requires that the static graphics data "in front of" the video data not be destroyed each time the video window is updated. A second concern with windowing systems operating on both video and graphics data is the formatting differences between the video and graphics data themselves since video is typically digitized into a YUV color space while graphics is digitized into an RGB color space. Hence, any combination video and graphics windowing system must have the capability of efficiently handling data within both the YUV and RGB formats.

Thus, due to the advantages of windowing, the need has arisen for efficient and cost effective windowing control circuitry. Such windowing circuitry should allow for the simultaneous processing of data received from multiple sources and in multiple formats. In particular, such windowing control circuitry should be capable of efficiently and inexpensively controlling the occlusion and/or overlay of video and graphics data in a windowing environment.

SUMMARY OF THE INVENTION

The principles of the present invention in general provide for the flexible control of graphics and video data in a display control environment. In particular, an entire frame of video data, graphics data, or a combination of both, may be stored in on-screen memory and rastered out with the generation of the corresponding display screen. A window of graphics or video data can then be stored in off-screen memory and retrieved when the raster scan generating the display reaches the desired position on the display for the video window. The window of data from off-screen memory can then be overlayed over the data being rastered out of the on-screen memory under one of three conditions. In a first mode, pixels from the off-screen memory are rastered only when the raster scan has reached the position on the display selected for the window. In a second mode, a window of data is rastered from the off-screen memory when the display raster scan has reached the display window position and graphics data being rastered from the on-screen memory matches a color key. In a third mode, the window data is rastered out of the off-screen memory when the data being output from the on-screen memory matches the color key, notwithstanding the position of the raster scan.

According to a first embodiment of the present invention, a graphics and video controller is provided which includes a dual aperture interface, each word associated with an address to a selected one of on-screen and off-screen areas of an associated unified frame buffer as either graphics or

video pixel data. Circuitry is provided for writing a word of the pixel data received by the interface to a one of the on-screen and off-screen memory areas corresponding to the address associated with the received word. Circuitry is also included for selectively retrieving graphics and video data from the on-screen and off-screen memory areas. A first pipeline is provided for processing graphics data retrieved from the frame buffer and a second pipeline is provided for video processing data retrieved from the frame buffer.

According to a second embodiment of the present invention, a controller is provided which includes a dual aperture port for receiving video and graphics data, each word of the data received with an address associated directing the word to be processed as either graphics or video data and off-screen memory spaces of a frame buffer. A second port is included for receiving real-time video data. Circuitry is provided for generating an address associated with a selected one of the memory spaces for each word of received real-time video data. Circuitry is included for writing selectively the words into the on-screen and off-screen memory spaces of the frame buffer. Circuitry is also provided for selectively retrieving the words of data from the on-screen and off-screen spaces as data is rastered for driving a display. A graphics backend pipeline processes ones of the graphics words of data retrieved from the frame buffer. A video backend pipeline is provided for processing ones of the video words of data retrieved from the frame buffer, the circuitry for retrieving always rastering a stream of graphics data from the frame buffer to the graphics pipeline and rastering video data to the video backend pipeline when a display raster scan reaches a display position of a video window. An output selector is included for selecting for output between words of data output from the graphics backend pipeline and words of data output from the video backend pipeline.

According to

a third embodiment of the present invention, a display system is provided which includes first and second parallel backend pipelines. A multi-format frame buffer memory is included having on-screen and off-screen memories each operable to simultaneously store data in graphics and video formats. A dual aperture port is provided for receiving both graphics and video data as directed by an address associated with each word of data received. Circuitry for writing is included for writing a word of video or graphics data into a selected one of the on-screen and off-screen areas of the multi-frame buffer. Memory control circuitry controls the transfer of data between the first and second [back-end] backend

pipelines and the frame buffer. The system further includes a display unit and overlay control circuitry for selecting for output to the display unit between data provided by the first backend pipeline and data provided by the second backend pipeline.

A fourth embodiment of the present invention comprises a display data processing system which includes circuitry for writing data into an on-screen space of a frame buffer and circuitry for writing data into an off-screen space of the frame buffer. A video pipeline is provided for processing video data output from a selected one of the on-screen and off-screen spaces. The video pipeline includes a first first-in/first-out memory for receiving selected pixel data from the selected space. The video pipeline also includes a second first-in/first-out memory disposed in parallel to the first first-in/first-out memory for receiving other selected data from the selected space in the frame buffer. An interpolator is provided as part of the video pipeline for generating additional data by interpolating data output from the first and second first-in/first-out memories. A graphics pipeline is

disposed in parallel to the video pipeline for processing graphics data output from a selected one of the on-screen and off-screen spaces. Finally, an output selector is provided for selecting between data output from the video pipeline and data output from the graphics pipeline.

The principles of the present invention allow for the construction of circuits and systems with substantial advantages over the prior art. Among other things, the principles of the present invention allow both graphics and video data to be stored in a single unified frame buffer and retrieved therefrom in a number of different ways. For example, a combination of graphics and video data may be stored in the on-screen memory and simply rastered out during screen refresh. In another case, an entire screen of graphics or video data may be stored in the on-screen memory while a window of graphics or video data is stored in the off-screen portion of memory. The window data can then be rastered out to selectively overlay a portion of the data being rastered out of the on-screen memory. The overlay may be controlled by either window display position with a match of the on-screen data being rastered out and a color key, or both.

The embodiments of the present invention provide for the efficient and inexpensive overlay of video and graphics data in a windowing environment. In particular, the use of color comparison to determine the overlay of data in a window region eliminates the need for precise x- and y-position data for the location of that window and allows for video cropping to be performed. Further, the use of graphics data to control overlay provides substantial advantages in that graphics data is less subject to the graininess and noise problems often found with video data. Further, the user is given total control of overlay operations when keying on graphics data because the graphics data is computer generated, whereas the video data is captured data.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a top level functional block diagram of a multi-media processing and display system embodying the principles of the present invention;

FIG. 2 is a more detailed functional block diagram of the VGA controller depicted in FIG. 1;

FIG. 3 is an expanded functional block diagram of portions of the controller of FIG. 2 with emphasis on the overlay control features;

FIG. 4A is a detailed functional block diagram of a first embodiment of the color comparison circuitry of FIG. 3;

FIG. 4B is a detailed functional block diagram of a second embodiment of the color comparison circuitry of FIG. 3; and

FIG. 5 is a detailed functional block diagram of a selected one of the video window position control circuits depicted in FIG. 3.

DESCRIPTION OF THE INVENTION

FIG. 1 is a high level functional block diagram of a multi-media processing and display system 100 operable to process and simultaneously display on a single display screen both graphics and video data according to the principles of the present invention. Display system 100 includes a central processing unit (CPU) 101 which controls the overall operation of system 100 and generates graphics data

defining graphics images to be displayed. CPU 101 communicates with the remainder of the system discussed below via a local bus 103. System 100 also includes a real-time video data source 104. A real time video stream may be presented to the system VGA controller 105 in one of two ways. First, video data source 104 may be coupled to local bus 103 and a video data stream introduced through dual aperture addresses. In this case, video source 104 will directly address the system frame buffer 107. Second, video source 104 may be coupled directly to VGA controller 105 via a dedicated bus 109 or "video port." In this instance, VGA controller 105 generates the required addresses into frame buffer 107. Real-time video source 104 may be, for example, a CD ROM unit, a laser disk unit, a videotape unit, television cable outlet or other video data source outputting video data in a YUV format. CPU 101 operates in conjunction with a system memory 108 which stores graphics and video data on a real-time basis. System memory 108 may be for example random access memory (RAM), floppy disk, hard disk or other type of storage device.

A VGA controller 105 embodying the principles of the present invention is also coupled to local bus 103. VGA controller 105 will be discussed in detail below; however, VGA controller 105 generally interfaces CPU 101 and video source 104 with a display unit 106 and a multiformat system frame buffer 107. Frame buffer memory 107 provides temporary storage of the graphics and video data during processing prior to display on display unit 106. According to the principles of the present invention, VGA controller is operable in selected modes to store graphics and video data together in frame buffer 107 in their native formats. In a preferred embodiment, the frame buffer area is partitioned into on-screen memory and off-screen memory. Frame buffer 107 is also a "unified" memory in which video or graphics data can be stored in either the on-screen or off-screen areas. In the preferred embodiment, display unit 106 is a conventional raster scan display device and frame buffer 107 is constructed from dynamic random access memory devices (DRAMs).

FIG. 2 is a more detailed functional block diagram of VGA controller 105. The primary circuitry blocks of VGA controller 105 include video front-end video pipeline 200, memory (frame buffer) control circuitry 201, CRT/window control circuitry 202, video window control registers 203, video [back-end] backend pipeline 204 and graphics

[back-end] backend pipeline 204 and graphics back-end pipeline 205. VGA controller 105 further includes a CPU interface 206 for exchanging instructions and data via a PCI or VL bus, such as local bus 103 in system 100, with CPU 101. A write buffer 207 and conventional graphics controller 208 allow CPU 101 to directly control data within frame buffer 107 via memory control circuitry 201.

In the preferred embodiment of system 100, CPU 101 can write video data and/or read and write graphics data to frame buffer 107 via CPU interface 206. In particular, CPU 101 can direct each pixel to the frame buffer using one of two maps depending on whether that pixel is a video pixel or a graphics pixel. In the preferred embodiment, each word of pixel data ("pixel") is associated with one of two addresses, one which directs interpolation of the pixel as a video pixel through video front-end pipeline 200 and the other which directs interpolation of the pixel as a graphics pixel through write buffer 207 and graphics controller 208. As a consequence, either video or graphics pixel data can then be input to CPU interface 206 from the PCI/VI bus through a single "dual aperture" port as a function of the selected address.

Data which is input through the video port 211 is address-free. In this case, video window controls 213 generates the

required addresses to either the on-screen memory area or the off-screen memory as a function of display location for the video window. In the preferred embodiment, window controls 213 generate addresses using the same video control registers 203 used to control retrieval of the video in the
 5 [back-end] backend pipeline (i.e., the screen x and y position registers 500 and 501 discussed below in conjunction with FIG. 5). When data is being received through both the CPU interface 206 and the VPORT 211 simultaneously, the data is interleaved into memory with the two write buffers 207 and 217
 10 buffering the data such that neither stream is interrupted or forced into a wait state at the source component (i.e., bus 103 or video source 104).

It should be noted at this point that frame buffer 107 includes at least two different data areas or spaces to which
 15 data can be directed by the given address (either CPU 103 or controls 213 generated.)

Each space can simultaneously store graphics or video data depending on the selected display configuration. The on-screen area corresponds to the display screen; each pixel rastered out of a given pixel
 20 location in the on-screen area defines a corresponding screen pixel. The off-screen area is used to store data defining a window for selectively overlaying the data from the on-screen memory, fonts and other data necessary by controller
 25 105. Further, as will be discussed [further] below, both graphics and video data may be rastered from frame buffer 107 and passed through video backend pipeline 204 while only graphics data is ever passed through graphics backend pipeline 205.

According to the principles of the present invention, there are alternate ways of storing and retrieving graphics and video data from unified frame buffer 107.

For example, CPU 103 may write a static graphics background into part of the on-screen memory with the remaining "window" in the on-screen memory area filled with
 35 playback video data. "Playback" video data can be either (1) live video data input from the VPORT; (2) YUV (video) data written through interface 206 by CPU 103; or (3) true color (5:5:5, 5:6:5, or 8:8:8) RGB graphics data (for example animation graphics data) written in through either the
 40 VPORT or interface 206. Similarly, a playback video background and a window of graphics data may be written into the on-screen area. In each of these cases, the data is rastered out as the display is without overlap: the video playback data
 45 is passed through [the video playback data is passed through] the video backend pipeline 204 as a function of display position by controls 202 and the graphics data passed through the graphics backend pipeline 205.

Windows of data retrieved from the off-screen memory can be retrieved and used to occlude a portion of the data
 50 being rastered out of the on-screen memory. For example, a window of playback data can be stored in the off-screen memory and a frame of static graphics data (either true color data or indices to CLUT 234) stored in the on-screen
 55 memory. In this case, the static graphics are rastered out of the on-screen memory without interruption and passed through the graphics backend pipeline 205. The window of data in the off-screen memory is rastered out only when the display position for the window has been reached by the
 60 display raster and is passed through video backend pipeline 204. As discussed below, data from the video backend pipeline 204 can then be used to selectively occlude (overlay) the data being output from the graphics backend pipeline 205. A window of static graphics data (true color or
 65 indices to the CLUT 234) can be stored in off-screen memory and used [of] to

overlay playback video from the on-screen memory[, the]. The playback video data is passed

through the video backend pipeline 204 and the window of static graphics data is passed through the graphics backend pipeline 205.

Bit block transfer (BitBLT) circuitry 209 is provided to allow blocks of graphics data within frame buffer 107 to be transferred, such as when a window of graphics data is moved on the display screen by a mouse. Digital-to-analog converter (DAC) circuitry 210 provides the requisite analog signals for driving display 106 in response to the receipt of either video data from video [back-end] backend pipeline 204 or graphics data from [back-end pipe line] backend pipeline 208.

In implementing the operations discussed above, video front-end pipeline 200 can receive data from two mutually exclusive input paths. First, in the "playback mode," playback (non-real time) data may be received via the PCI bus through CPU interface 206. Second, in the "overlay emulation mode" either real-time or playback video may be received through the video port interface 211 (in system 100 video port interface 211 is coupled to bus 109 when real-time data is being received). The selection of video from the PCI bus or video from video port interface 211 is controlled by a multiplexer 212 under the control of bits stored in a video front-end pipeline control register within video control registers 203. In the playback mode, either CPU 101 or a PCI bus master controlling the PCI bus provides the frame buffer addresses allowing video front-end pipeline 200 to map data into the frame buffer separate and apart from the graphics data. In the overlay emulation mode, overlay input window controls 213 receives framing signals such as VSYNC and HSYNC, tracks these sync signals with counters to determine the start of each new frame and each new line, generates the required addresses for the real-time video to the frame buffer space using video window position data received from window controls 222 (as discussed above, in the preferred embodiment, video data is always retrieved from either the on-screen or off-screen memory and passed through video back-end pipeline 204 as a function of display position) and thus the position data from controls 222 is used to both write data to memory and retrieve data therefrom). In general, overlay input video control windows are controlled by the same registers which control the [back-end] backend

video pipeline 204, although the requisite counters and comparators are located internal to overlay input video control circuitry 213.

Video front-end pipeline 200 also includes encoding circuitry 214 that is operable to truncate 16-bit YUV 422 data into an 8-bit format and then pack four such 8-bit encoded words into a single 32-bit word which is then written into the video frame buffer space of frame buffer 105. Conversion circuitry 215 is operable to convert RGB 555 data received from either the CPU interface 206 and the PCI bus or VPORT I/F 211 into YCrCb (YUV) data prior to encoding by encoding circuitry 214. Conversion circuitry 215 allows graphics data (for example in a 5:5:5 or 5:6:5 format) to be introduced through the VPORT or graphics data to be converted, packed and stored in a YUV format in the off-screen memory space by CPU 101. For a more complete description of encoder 214 and the associated decoder 225 of video pipeline 204, reference is now made to incorporated copending coassigned application Ser. No. 08/223,845. The selection and control of the encoding circuitry 214 and conversion circuitry 215 is implemented through multiplexing circuitries 212 and 216, each of which are controlled by bits in the video control registers. Finally, video front-end pipeline 200 includes a write buffer/FIFO 217 which in one embodiment acts as a write buffer and in an alternate embodiment acts as a FIFO for the video

backend pipeline 204. In embodiments where buffer 217 acts as a write buffer for then Y, zooming on the [back-end,] backend, as discussed below is by replication. In embodiments where buffer 217 operates as a FIFO, then the VPORT and front and end color conversion by converter circuitry 215 are not used for writing data to frame buffer 107.

Memory control circuitry 201 includes an arbiter 218 and a memory interface 219. Arbiter 218 prioritizes and sequences requests for access to frame buffer 107 received from video front-end pipeline 200, graphics controller 208 and bit block transfer circuitry 209. Arbiter 218 further sequences each of these requests with the refresh of the display screen of display 106 under the control of CRT controller 202. Memory interface 219 controls the exchange of addresses, data, and control signals (such as RAS, CAS and read/write enable) to and from frame buffer 107.

CRT control/video window control circuitry 202 includes the CRT controller 220, window arbiter 221, and video display window controls 222. CRT controller 202 controls the refresh of the screen of display 106 and in particular the rastering of data from frame buffer 107 to display unit 107 through DAC 210. In the preferred embodiment, CRT controller 220, through arbiter 218 and memory interface 219, maintains a constant stream of graphics data into graphics backend pipeline 205 from memory; video or playback graphics data is rastered out only when a window has been reached by the display raster as determined by display position controls of window controls 222 (see FIGS. 3 and 5 and accompanying text) and CRT controller 220. As will be discussed in further detail below, the display of windows within the display according to the principles of the present invention is controlled in part by circuitry 202.

Video [back-end] backend

pipeline 204 receives a window of graphics video data defining a display window from the on-screen or off-screen spaces in frame buffer 107 through a pair of first-in/first-out memories 223 and 217 (in embodiments where buffer 217 is acting as FIFO B). In the preferred embodiment, each FIFO receives the data for every other display line of data being generated for display on the display screen. For example, for a pair of adjacent lines $n-1$ and $n+1$ in memory (although not necessarily adjacent on the display) for the display window, FIFO 223 receives the data defining window display line $n-1$ while FIFO 224 receives the data defining window display line $n+1$. When buffer 217 is used as FIFO B, writes through video front end pipeline 200 are made through write buffer I 207 and multiplexer 235. Alternatively, if buffer 217 is used as write buffer II, then FIFO B is not implemented and only a single stream is processed by video [back-end] backend

pipeline 204 (no Y interpolation is performed and Y expansion is by replication). As will be discussed further below (assuming both FIFO A and FIFO B are being used), one or more display lines, which falls between line $n-1$ and line $n+1$, may be selectively generated by interpolation. Decoder circuitry 225 receives two 32-bit packed words (as encoded by encoder 214), one from each adjacent scan line in memory, from FIFOs 223 and 217. Each 32-bit word, which represents four YCrCb pixels, is expanded and error diffused by decoder 225 into four 16-bit YCrCb pixels. In modes where video data is stored in the frame buffer in standard 555 RGB or 16 YCrCb data formats, decoder block 225 is bypassed.

[Back-end] Backend

video pipeline 204 further includes a Y interpolator 226 and X interpolator 227. In the preferred embodiment, during Y zooming (expansion) Y interpolator 226 accepts two vertically adjacent 16-bit RGB or YCrCb pixels from the decoder 225 and calculates one or more resampled output pixels using a four subpixel granularity. X interpo-

later 227 during X zooming (expansion) accepts horizontally adjacent pixels from the Y interpolator 226 and calculates one or more resampled output pixels using a four subpixel granularity. For data expansion using line replication, Y interpolator 226 is bypassed. Y interpolator 226 and X interpolator 227 allow for the resizing of a video display window being generated from one to four times.

The output of X interpolator 227 is passed to a color converter 228 which converts the YCrCb data into RGB data for delivery to output multiplexer 304. To reiterate, if graphics data is passed through video pipeline converter 228 is not used.

[Back-end] Backend

video circuitry 204 further includes pipeline control circuitry 229, overlay control circuitry 230 and output multiplexer 231. Pipeline control circuitry 229 controls the reading of data from video FIFOs 223 and 217, controls the generation of interpolation coefficients for use by X and Y interpolators 226 and 227 to resize the video window being pipelined, and times the transfer of data through the pipeline. Overlay control circuitry 230 along with control circuitry 202, controls the output of data through output multiplexer 231, including the overlay of the video window over the graphics data output through the graphics [back-end] backend.

pipeline 205. A pixel doubler is provided to double the number of pixels being generated such that a 1280x1024 display can be driven.

Graphics [back-end] backend

pipeline 205 includes a first-in/first-out memory 232, attribute controller 233, and color look-up table 234. Each 32-bit word output from graphics FIFO 232 is serialized into either 8-bit, 16-bit or 24-bit words. The 8-bit words, typically composed of an ASCII code and an attribute code, are sent to attribute controller 233. When 16-bit and 24-bit words, which are typically color data, are serialized, those words are sent directly to overlay controls 230. Attribute controller 233 performs such tasks as blinking and underlining operations in text modes. The eight bits output from attribute controller 233 are pseudo-color pixels used to index CLUT 234. CLUT 234 preferably outputs 24-bit words of pixel data to output multiplexer 231 with each index. When video data is being pipelined through graphics backend pipeline 205 from the on-screen memory, CLUT 234 is bypassed.

The eight bit pseudo-color pixels [are] output from attribute controller 233 are also sent to overlay controls 230. In the preferred embodiment, data is continuously pipelined from on-screen memory through graphics [back-end] backend

pipeline 205 to the inputs of output multiplexer 231. Window data from off-screen memory however is only retrieved from memory and pipelined through video backend pipeline 204 when a window is being displayed. In other words, when a window has been reached, as determined by control bits set by CPU 101 in VW control registers 222, video window display controls 222 generate addresses to retrieve the corresponding data from the off-screen memory space of frame buffer 107. Preferably, video FIFOs 223 and 224 are filled before the raster scan actually reaches the display window such that the initial pixel data is available immediately once the window has been reached. In order to insure that graphics memory data continues to be provided to graphics [back-end] backend pipeline 205, video window display controls 222 "steal" page cycles between page accesses to the graphics memory. It should be noted that once the window has been reached the frequency of cycles used to retrieve window data increases over the number used to fill the video FIFOs when outside a window. When the frequency of window page accesses increases, video window display controls 222/arbiter 221 preferably "steal" cycles from page cycles being used to write data into the frame buffer.

FIG. 3 is a more detailed functional block diagram emphasizing the circuitry controlling the overlay of data from graphics pipeline 205 with window data from video pipeline 204. As discussed briefly above, the inputs to output multiplexer 231 are data from video [back-end] backend

pipeline 204 (pixel doubler 237), 16 or 24-bit color data directly from graphics back-end pipeline 205 serializer 236 and 24-bit color data from the color look-up table 234. The output of data to DAC 210 through output multiplexer 231 is controlled by a latch 301 clocked by the video clock (VCLK). The remaining circuitry shown in FIG. 3, which will be discussed in further detail below, provide the necessary control signals to the control inputs of output multiplexer 231 to select between the video and graphics pipelines.

The graphics pseudo-pixels output from attribute controller 233 and the 16-bit or 24-bit graphics or video data output directly from serializer 236 are provided to the inputs of color comparison circuitry 302. Also input to color comparison [circuit] circuitry

302 are 16 or 24-bit overlay color key bits stored in overlay color key register 303. Overlay color key register 303 resides within the address space of, and is loaded by, CPU 101. Depending on the mode, color comparison circuitry 302 compares selected bits from the overlay color key register 303 with either the 8 bits indexing look-up table 234 in the color look-up table mode (pseudo-color mode) or the 16-bits (24-bits in the alternate embodiment) passed directly from serializer 236. It should be noted that in the illustrated embodiment, overlay color key register 303 holds [24-bits of] 24

of overlay color key bits, eight each for

red, green, and [blue/index] blue index comparisons. The specific overlay color key bits compared with the input graphics data are provided in Table I:

MODE	OVERLAY COLOR KEY BITS COMPARED			
CLUT	—	—	—	Blue/Index
Index	—	—	—	<7:0>
5:5:5	Red<4:0>	Green<4:0>	Blue<4:0>	Blue<4:0>
5:6:5	Red<4:0>	Green<5:0>	Blue<4:0>	Blue<4:0>
8:8:8	Red<7:0>	Green<7:0>	Blue<7:0>	Blue<7:0>

As shown in FIG. 4A, a first embodiment of color comparison circuitry 303 performs the comparisons set forth in Table I as a set of XNOR operations in series with an AND operation. FIG. 4A depicts first comparison circuitry 400 for comparing the 8-bits of graphics pixels received in the look-up table mode from attribute controller 233 with the 8-bit blue/index overlay key bits being held in overlay key register 303. Second comparison circuitry 401, performs the required comparisons of Table I for the 16-bit data or 24-bit received from serializer 236, in, either a 5:5:5, 5:6:5, or 8:8:8 format. An overlay register 402 includes a bit loaded by CPU 101 which is used by a selector 403, depending on the mode, to select for output, either the result of the comparisons being made by comparison circuitry 400 in the color look-up table mode or the results of the comparisons being made by comparison circuitry 401. In the illustrated embodiment, color comparison circuitry 303 processes data on a pixel-by-pixel basis and is resynchronized with both the

graphics [back-end] backend pipeline 205 and the video back-end pipeline 204 by having its outputs latched to the video clock (VCLK) by latches 404.

The output of color comparison circuitry 303 is passed to the "K" control input of overlay control multiplexer 304. The "P" control input to multiplexer 304 is provided from pixel position comparison circuitry 305. The data inputs to multiplexer 304 are coupled to an 8-bit overlay OP Code

(OOC) register 306. The output of multiplexer 304 is used as one control input to output multiplexer 304, which along with a single bit set by CPU 101 into output control register 307, selects which of the data received at the data inputs of multiplexer 231 will be output to DAC 210.

Pixel position comparison circuitry 305 includes three inputs coupled respectively to video window 1 position control circuitry 308, CRT position control circuitry 309 and video window 2 position control circuitry 310. In the illustrated embodiment, CRT position controller 309 is located within CRT controller 220 while video window 1 position control circuitry and video window 2 position control circuitry 310 are located within video display window controls 222 (FIG. 2). CRT position control circuitry 309 includes counters [which,] which

track the position of the current pixel being generated for display. In the preferred embodiment, CRT position control circuitry 309 includes at least an x-position counter which tracks the generation of each pixel along a given display line and a y-position counter which tracks the generation of each display line in a screen. The x-position counter may for example count pixels by counting each VCLK period between horizontal synchronization signal (HSYNC) controlling display unit 106. The y-position counter may for example count each HSYNC signal occurring between each vertical synchronization signal (VSYNC) controlling the screen generation on display unit 106. FIG. 4B is an alternate embodiment of the color comparison circuitry of FIG. 3. In a first mode, 8 bits [are]

from attribute controller 233 are passed through multiplexer to comparator 406. Comparator 406 compares the received eight bits with an 8-bit color key in color key register 408; when the received 8-bits equal the 8-bit key 1, the output of comparator 406 goes active (high). In the first mode, control signal 16BITGR is high (and the output of NOR gate 409 is consequently high) and an active output from comparator 406 is gated through AND gate 410. The output of AND gate 410 is passed to AND gate 411 and gated with the output from the pixel comparison circuitry 305. The output of AND gate 411 goes directly to the "B" control input of selector 231 (in this embodiment multiplexer 304 and register 306 are eliminated). Thus, when the 8-bit graphics pixels output from attribute controller 233 of graphics backend 205 matches the 8-bit color key 1 and the window has been reached as determined by pixel comparison circuitry 305, the pixel data output from video backend 204 are passed through selector 231.

In a second mode, 16 bits are received from serializer 236. The eight LSBs are passed through multiplexer 405 to comparator 406 and the eight MSBs passed to comparator 407. Control signal 16BITNG is set high. When the LSBs equal key 1 in color register key 408 and the 8 MSBs equal key 2 in color key register 408, the outputs from comparators 406 and 407 are active (high). The output of AND gate 411 then goes high when the output from pixel comparison circuitry 305, which is coupled to the "B" control input of selector 231, goes high. Thus, when the 16-bit pixel data output from serializer 236 of graphics backend 205 matches the 16-bit color key (keys 1 and 2) and a window has been reached, the output pixel data from video backend 204 are passed through selector 231.

FIG. 5 is an expanded functional block diagram of the video window position control circuits 308 and a corresponding portion of the gating of pixel position compare circuitry 305. Each position control circuit 310/312 is coupled to a screen position x-register 500 and a screen position y-register 501, and includes a screen x-position counter 502, and a screen y-position counter 503. In the

preferred embodiment, registers 500 and 501 are located within video window control registers 203. For the window corresponding to the given video window control circuitry 308 or 310, registers 500 and 501 are loaded with a value representing the x and y screen position of the pixel in the upper left corner of that window (the starting pixel). Screen x-register 500 and screen y-register 501 in the preferred embodiment are loaded by CPU 101. The screen x-position counter 502 counts down from the value held in screen x-register 500 with each video clock when P is high for each display line and resets with each display horizontal synchronization signal (HSYNC) (Note that when P is high the CRT count matches the position count). Screen y-position counter 503 counts down from the value set into screen y-register 501 for each horizontal sync signal (HSYNC) at the start of each display line and resets with each VSYNC at the start of each new screen (The position counters are allowed to count only when they match their perspective CRT). The counts values in the counters of CRT position control circuitry 309 are compared pixel by pixel with the counts in screen x-position counter 502 and screen y-position 503 of each video window position control circuitry 308 and 310. When both the x and y counts in the counters of CRT position control circuitry 309 match the corresponding x and y counts in respective counters 502 and 503 of either video window control circuitry 308 or 310, the control signal P to multiplexer 304 is activated. The activation of control signal P indicates that the raster scan on display 106 has reached the position of a pixel within the [window] window,

and data from video pipeline 205 may be painted depending on the value being held in overlay OP Code (OOC) register 306 and the K control inputs to multiplexer 304.

A 4-bit OP Code loaded by CPU 101 into overlay OP Code register 306 in conjunction with the control signals applied to the "P" and "K" control inputs to multiplexer 304 control the presentation of an active (assumed high in the illustrated embodiment) control signal to the "B" control input to output multiplexer 231. The other ("A") input to output multiplexer 231 receives a bit from overlay mode register 402 (FIG. 4), as loaded by CPU 101. In the illustrated embodiment, the selection between the streams from the graphics and video backends at the 0,1,2 inputs to output multiplexer 304 in response to the signals presented at the corresponding control inputs "A" and "B" is in accordance with Table II:

Control Input A	Control Input B	Selected Stream
0	0	Graphics or video pixels from graphics pipeline 205
1	0	Graphics pixels from CLUT 234 at input 1
0	1	Video or graphics from video backend 204
1	1	

The OP Codes used in the illustrated embodiment, the effective overlay and the corresponding inputs to the control inputs of multiplexer 304 are listed in Table III (active state is assumed[:]):

Overlay Op Code Register 309 Value	Multiplexer 307 Control Inputs	Effect	
0	N/A	Pixels passed only from graphics pipeline 205	5
A	Input P active	Paint pixels from video backend pipeline 204 only inside video window VDW _n	10
8	Inputs K and P active	Paint from video backend pipeline 204 window VDW _n when color key matches	15
C	Inputs K active	Paint from video backend pipeline 204 if color key matches	20

In the illustrated embodiment, if a 0h is written into OOC register 306 by CPU 101, only pixels from graphics pipeline 205 are pipelined through multiplexer 304. In this case any signals applied to the P and K control inputs to multiplexer 304 have no effect (i.e., will not result in a high output from multiplexer 304). In the illustrated embodiment, if an Ah is written into OOC register 306, pixels from video pipeline 204 will be passed to DAC 210 only when pixel position comparison circuitry 305 determines that the raster scan has reached a pixel in the window and hence the control signal going to the P input of multiplexer 304 has been activated. If on the other hand, an 8h is written into OOC register 306, data is passed through output multiplexer 231 to DAC 210 when pixel position comparison circuitry 305 determines that the raster scan has reached a pixel on the display screen within the window and color compare circuitry 302 has determined that the incoming data from graphics pipeline 205 matches the overlay color key held in overlay color key register 303. In this case, the data from video pipeline 204 is passed to DAC 210 when both the P and the K inputs to multiplexer 304 are active. Finally, when an OpCode of C is programmed into OOC register 306, data from video pipeline 204 is passed if the incoming data from graphics pipeline 205 matches the overlay color key held in overlay color key register 303. In this case, the activation of the K control input activate the output of multiplexer 304 to switch the input of multiplexer 231 to pass the corresponding video pixels.

Display control circuits embodying the principles of the present invention have substantial advantages over the prior art. In particular, output control circuits built in accordance with the principles of the present invention allow for the flexible display of both graphics and video on the same screen. In particular, pixel position comparison circuitry 305 along with video window position control circuits 308 and 310 and CRT position control circuitry 309 allow for [a]

one or more windows from off-screen memory to be generated in specific areas of a display screen to the exclusion of any simultaneously generated data from on-screen memory. Further, color comparison circuitry 302 operating in conjunction with an overlay color key written into overlay color key register 303 allows window data to be presented on the display screen, to the exclusion of any concurrently generated graphics data, without the need for precise x- and y-position data for the window. Finally, the use of the graphics data from the graphics pipeline 205 to control the output overlay provides additional advantages since the video data can be subject to graininess and noise.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations [an] can be made herein without departing from the spirit and scope of the invention
5 as defined by the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230

is claimed is:

1. A single integrated graphics and video controller adapted for driving a display sequentially

comprising:

an interface for receiving words of pixel data, each said word associated with an address buffer;

10 circuitry for writing each said word of said pixel data received by said interface to a one of on-screen and off-screen memory areas of a frame buffer;

circuitry for selectively retrieving

as data is provided for display,

said words from said

on-screen and off-screen areas;

15 a first pipeline for substantially continuously processing words of graphics data retrieved from said frame buffer; and

a second pipeline for processing words of video data retrieved from said frame buffer so that the

video data is ready for display once a display raster scan reaches a display position of a window.

2. The controller of claim 1 and further comprising output

20 selection circuitry for selecting for output between graphics data received from said first pipeline and data received from said second pipeline, said selection circuitry operable to:

in a first mode, pass data from said

[first pipeline:] first pipeline; and

25 in a second mode, pass data from said second pipeline when said data corresponds to a selected display position of a display window.

3. The controller of claim 2 wherein said selection circuitry is further operable to:

30 in a third mode, pass data from said second pipeline when said data corresponds to said selected display position of said display window and data from said first pipeline match a color key.

35 4. The controller of claim 3 wherein said selection circuitry is further operable in a fourth mode to pass data from said second pipeline when data from said first pipeline match a color key.

5. The controller of claim 1 wherein said circuitry for retrieving maintains a stream of graphics data to said first

40 pipeline and provides video data to said second pipeline when a display raster scan reaches [said display] a display [said window] a window. position of

6. The controller of claim 1 and further comprising:

a video port for receiving real-time video data; and

45 circuitry for generating an address to said memory at which said real-time video data is to be stored.

7. The controller of claim 1 wherein said second pipeline includes a first first-in-first-out memory for receiving data

50 for a first display line of pixels in memory and a second first-in-first-out memory for receiving data from a second display line of [pixels memory] pixels in memory.

8. The controller of claim 7 wherein said first display [line adjacent] line is adjacent

in memory to said second display line.

9. The controller of claim 7

further comprising output selection circuitry

wherein said output selection

55 circuitry comprises:

an output selector for selecting between data from said second pipeline and data from said first pipeline in response to a selection control signal;

60 a register for maintaining a plurality of overlay control bits;

window position control circuitry for selectively generating a position control signal when a word of said data stream from said second pipeline falls within a display window;

65 color comparison circuitry for comparing words of said data stream from said first pipeline with a color key and

OFFICIAL RECORD

for providing in response a color comparison control signal; and

a control selector for selectively providing [a] said

selection control signal in response to said overlay control bits in said register and at least one of said position control and color comparison control signals. 5

10. The controller of claim 9 wherein said window position control circuitry comprises:

window position counters operable to increment from initial count values corresponding to a starting pixel of a display window as data representing each pixel in a display screen is pipelined through said overlay control circuitry; 10

screen position counters operable to count as data representing each pixel in said display screen is pipelined through said overlay control circuitry; and 15

comparison circuitry operable to compare a current count in said window position counters and a current count in said screen position counters and selectively generate said position control signal in response. 20

11. The controller of claim 9 wherein said color comparison circuitry comprises:

a color key register for storing bits composing said color key; and

a plurality of AND-gates for comparing said words of said graphics data stream with bits of said color key. 25

12. The controller of claim 1 wherein said interface includes a dual-aperture port.

13. A single integrated controller comprising:

circuitry for writing selectively, on a word by word basis, 30

data into [s] a each word of received

selected one of on-screen and off-screen memory spaces of a frame buffer;

a first port for receiving video and graphics data, a word of said data received with an address of said memory spaces directing said word to be processed as a word of video data or a word of graphics data; 35

a second port for receiving real-time video data;

circuitry for generating an address associated with a selected one of said memory spaces for a word of said real-time video data; 40

circuitry for selectively retrieving said words of data on a word by word basis from said on-screen and off-screen memory spaces as data is rastered for driving a display in a sequential fashion; 45

a graphics backend pipeline for processing ones of said words of data representing graphics data retrieved from said frame buffer; 45

a video backend pipeline, separate

from said graphics backend pipeline,

for processing other ones of said words of data representing video data retrieved from said frame buffer, said circuitry for retrieving always rastering a stream of data from said frame buffer to said graphics backend pipeline and rastering video data to said video backend pipeline [when] so that the 50

video data is ready for display once

a display raster scan reaches a display position of a window; and 55

output selector circuitry for selecting for output between words of data output from said graphics backend pipeline and words of data output from said video backend pipeline. 60

14. The controller of claim 13 wherein said output selector circuitry

is further operable to select between graphics data output from a color look-up table and true color data output from said graphics pipeline.

15. The controller of claim 13 wherein said output selector circuitry

is operable to:

in a first mode, pass only a word of data output from said graphics pipeline; 65

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED
DATE 08-14-2010 BY 60322
UCBAW/STP/STP/STP/STP/STP

in a second mode, pass a word of data output from said video pipeline when said display raster scan has reached a display position corresponding to a window and a word of data from said graphics pipeline when said display raster scan is in any other display position;

5 in a third mode, pass a word of data output from said video pipeline when said display raster scan has reached a display position corresponding to a window and a corresponding word of data from said graphics pipeline matches a color key and a word of data from said graphics pipeline when said display raster scan is in any other display position; and

10 in a fourth mode, pass a word of data from said video pipeline when said corresponding word of data from said graphics pipeline matches a color key and a word of data from said graphics pipeline when said [display raster scan is in any other display position] corresponding word does not match said color key.

16. The controller of claim 13 wherein said video pipeline includes a first first-in-first-out memory for receiving a plurality of words of data for a first display line of pixels in memory and a second first-in-first-out memory [or] for receiving a plurality of words of data [from] for a second display line of pixels in memory.

17. The controller of claim 16 wherein said first display line is stored adjacent in memory to said second display line.

25 18. The controller of claim 13 wherein said output selector circuitry comprises:

a control selector having a plurality of control inputs coupled to a register, said register storing a plurality of overlay control bits;

30 window position control circuitry coupled to a first control input of said control selector, said window position control circuitry operable to selectively provide a first control signal to said first control input when a word of data being pipelined through said video pipeline falls within a display window;

35 color comparison circuitry operable to compare a word of data being pipelined through said graphics pipeline with a color key and provide in response a second control signal to a second control input of said control selector; and

40 wherein said control selector is operable to provide an output selection control signal in response to at least one of said first and second control signals and said overlay control bits being stored in said register.

45 19. The circuitry of claim 18 wherein said output selector circuitry further includes a third control input coupled to certain bits of said graphics pipeline, said output selector circuitry further

operable to select between data on said respective video and graphics pipelines in response to said certain bits presented to said selector circuitry.

20. The circuitry of claim 18 wherein said window position control circuitry comprises:

50 a window x-position counter operable to count from a loaded x-position value in response to a video clock, said x-position counter reloading in response to a display horizontal synchronization signal;

60 a window y-position counter operable to count from a loaded y-position value in response to said horizontal synchronization signal, said y-position counter reloading in response to a display vertical synchronization signal;

CRT position circuitry operable to maintain counts corresponding to a current display pixel; and

65 comparison circuitry operable to compare current counts in said window counters with said current counts held

in said CRT position circuitry and generate in response said first control signal.

21. The circuitry of claim 20 wherein said window position control circuitry further comprises an x-position register for holding said x-position value for loading into said x-position counter and a y-position register for holding said y-position value for loading into said y-position counter.

22. The circuitry of claim 13 wherein said color comparison circuitry comprises:

- a color key register for storing a plurality of color key bits;
- and
- a plurality of XNOR-gates each having at least one input coupled to a bit position in said color key register and at least one input coupled to said graphics data path.

23. The circuitry of claim 13 wherein said video pipeline comprises:

- a first-in/first-out memory for receiving a first stream of words of data from said frame buffer;
- a second first-in/first-out memory disposed in parallel with said first first-in/first-out memory for receiving a second stream of words of data from said frame buffer;
- and

interpolation circuitry for selectively generating an additional word of data by interpolating a word of said first stream and a word of **said second**

stream data output from said first and second first-in/first-out memories.

24. The controller of claim 13 wherein said first [pore] port comprises a dual-aperture port.

25. A display system comprising:
- a first backend pipeline for processing data;
 - a second backend pipeline for processing graphics data disposed in parallel to said first processing pipeline;
 - a multi-format frame buffer memory having on-screen and off-screen areas each operable to

to allow said frame buffer to simultaneously store data in graphics and video formats;

[a] an

input port for receiving both graphics and video data, each word of said data associated with an address directing said word to be processed as either graphics or video data;

circuitry for writing a word of said playback data into a selected one of said areas of said multi-format memory; memory control circuitry for controlling the transfer of data between said first backend pipeline and said frame buffer and between said second backend pipeline and said frame buffer;

a display unit; and

overlay control circuitry for selecting for output to said display unit between data provided by said first backend pipeline and data provided by said second backend pipeline.

26. The display system of claim 25 wherein said second backend pipeline includes:

- a first first-in-first-out memory for receiving first selected data;
- a second first-in-first-out memory disposed in parallel to said first first-in-first-out memory for receiving second selected data; and

interpolation data for generating additional data by interpolating data output from said respective first and second first-in-first-out memories.

27. The display system of claim 26 wherein said second backend pipeline further comprises color conversion circuitry for converting data received from said frame buffer in a video format to a graphics format.

28. The display system of claim 25 [and]

further comprising
a video front-end pipeline for inputting video data into a
selected one of on-screen and off-screen spaces of said frame
buffer comprising:

- 5 a video data port for receiving video data from a real time
data **source; and**
input control circuitry for receiving framing signals asso-
ciated with said real time data and generating corre-
sponding addresses to said selected one of said spaces
10 in response.

29. The display system of claim 28 wherein said video
front-end pipeline further comprises encoding circuitry for
packing said video data prior to storage in said selected one
of said
spaces.

- 15 30. The display system of claim 28 wherein said video
front-end pipeline further [comprising] comprises
multiplexing circuitry
for selecting between video data received through said video
data port and data received from [said] a dual

aperture port.
31. The display system of claim 30 wherein said video
front end pipeline further comprises conversion circuitry for
20 converting graphics data received through said dual-aperture
port to a video format for storage in said selected one of said
spaces.

32. The display system of claim 25 wherein said first
backend pipeline processes playback video.

- 25 33. The display system of claim 25 wherein said input port
comprises a dual-aperture input port.

34. A single integrated
display data processing system comprising:

- circuitry for writing data into an on-screen space of a
frame buffer;
- 30 circuitry for writing data into an off-screen space of said
frame buffer;
- a video pipeline for processing data output from a selected
one of said on-screen and off-screen spaces comprising:
- 35 a first first-in-first-out memory for receiving selected
data from said selected space;
- a second first-in-first-out memory disposed in parallel
to said first first-in-first-out memory for receiving
other selected data from said selected space; and
an interpolator for generating additional data by inter-
40 polating data output from said respective first and
second first-in-first-out memories;

a graphics pipeline disposed in parallel to
and separate from

- .said video
pipeline for processing data output from a selected one
of said on-screen and off-screen spaces; and
- 45 an output selector for selecting between data output from
said video pipeline and data output from said graphics
pipeline.

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED
DATE 11-03-2001 BY 60322 UCBAW

COLUMN 18 CONTINUED

35. The system of claim 34 [and] further comprising
selection control circuitry for generating an output control
50 signal for controlling said output selector comprising:
a control selector having a plurality of data inputs coupled
to a register, said register for storing a plurality of
overlay control bits; and
55 color comparison circuitry operable to compare bits of
data output from said graphics pipeline with a color key
and provide in response a control signal to a control
input of said control selector.
36. The system of claim 34 [and] further comprising
60 window position control circuitry operable to provide a
second control signal to a second control input of said
control selector when data from said video pipeline falls
within a display window.
37. A single integrated
display controller comprising:
65 circuitry for selectively retrieving data from an associated
multi-format frame buffer, the frame buffer having
separate storage locations respectively operable for allowing
for simultaneously
[snoring] storing
graphics and video data;
in, said frame buffer;

a first pipeline for processing words of graphics data selectively retrieved from said frame buffer; and

a second pipeline, separate from the first pipeline,

for processing words of video data selectively retrieved from said frame buffer.

38. The controller of claim 37 wherein said first and second pipelines are disposed in parallel and concurrently process data.

39. The controller of claim 38 [and]

further comprising output selection circuitry for selecting for output between graphics data received from said first pipeline and video data received from said second pipeline.

40. The controller of claim 37 wherein said frame buffer is partitioned into on-screen and off-screen areas, each of said on-screen and off-screen areas operable to allow the buffer to

simultaneously store both graphics and video data.

41. The controller of claim 37 wherein said circuitry for selectively retrieving is operable to retrieve a substantially

constant stream of graphics data from said frame buffer and provide said stream of graphics data to said first pipeline.

42. The controller of claim 41 wherein said circuitry for selectively retrieving is operable to retrieve at least one said word of video data from said frame buffer and provide said at least one word of said video data to said second pipeline, only when said display controller is generating a video display window.

43. A display controller for interfacing a multi-format frame buffer and a display device, the multi-format frame buffer having on-screen and off-screen areas each operable for simultaneously storing both graphics and video pixel data in the frame buffer,

said display controller comprising:

circuitry for selectively retrieving pixel data from a selected one of said on-screen and off-screen areas of said frame buffer;

a graphics backend pipeline for processing graphics data retrieved from said selected one of said areas of said frame buffer;

a video backend pipeline for processing video data retrieved from said selected one of said areas of said frame buffer; and

5 an output selector for selectively passing to said display device data received from said graphics or video backend pipelines.

44. The display controller of claim 43 wherein said circuitry for selectively retrieving is operable to retrieve at
10 least one said word of video data from said frame buffer and provide said at least one said word of video data [no] to

said second pipeline only when said display controller is generating a video display window.

45. The display controller of claim 43 wherein said output
15 selector is operable to:

in a first [modes] mode

pass data from said graphics pipeline; and

in a second [modes] mode

pass data from said video pipeline

when a display position corresponding to a video
20 display window has been reached.

46. The display window of claim 43 wherein said output selector is operable to:

in a first mode, pass data from said graphics pipeline; and

25 in a second mode, pass data from said video pipeline when a display position corresponding to a video display window has been reached and data from said graphics pipeline match a color key.

47. The display controller of claim 43 wherein said output
30 selector is operable to:

in a first mode, pass data from said graphics pipeline; and

in a second mode, pass data from said video pipeline when data from said graphics pipeline matches a color
35 key.

48. The controller of claim 42 in which graphics data is substantially

continuously retrieved for a display while video data is retrieved only for the video display window.

* * * * *

[57]

ABSTRACT

A graphics and video controller 105 is provided which includes a dual aperture interface 206 for receiving words of graphics and video pixel data, each word of such data associated with an address directing that word to be processed as either graphics or video data. Circuitry 200, 201, 202, 207, 208 is provided for writing a word of the pixel data received from the interface 206 to a one of the on- and off-screen memory areas corresponding to the address associated with the received word. Circuitry 201, 202 is provided for selectively retrieving graphics and video data from the on-screen and off-screen memory areas. A first pipeline 205 is provided for processing data received from the on-screen area of frame buffer 107 while a second pipeline 204 is provided for processing data retrieved from the off-screen area of the frame buffer.

105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000







FIG. 4A








FIG. 3

FIG. 4B

